SPRAY EXPERT

www.spray-expert.ru
www.airflow-expert.ru
+7 (495) 125-06-83
req@spray-expert.ru

Accessories for Whisperblast Multiple Spray Nozzles

Ball joint

- For moveable assembly of low-noise flat jet and round jet nozzles
- Swiveling range: 30 degrees any direction
- Durable metal version, without wear-prone gaskets

Ball joint with thread connection

Ball joint with welding connection







Rotating joint
Ordering no.:
095.016.56.07.21

- Material polypropylene
- Swivelling on one plane
- Less expensive alternative to metal ball joints
- Swivelling range 90° left/right

G1: NPT 1/4 inside thread
G2: 3/8 BSPP outside thread

Connection	Ordering no. Type	Material no. 16 1.4305/1.4571 303SS/316 SS	Material no. 16 1.4305	Material no. 30 Brass	Code	D1	D2	G1	G2	LG1	LG2	L	Hex1	Hex2	Hex3	Weight (brass)
Ball joints with thread connection	092. 020	-	○	○	AD	-	-	G1/4	G1/4	12.0	11,5	60,3	27	27	17	60 g
	092. 021	-	○	○	AF	-	-	G3/8	G1/4	12.0	11,5	58,3	27	27	17	80 g
	092. 030	-	○	○	AF	-	-	G3/8	G3/8	12.0	12,0	56,7	27	30	19	80 g
Ball joints with welding connection	092. 020	○	-	-	SD	20,0	15,0	-	G1/4	-	11,5	64,3	-	27	17	60 g
	092. 030	○	-	-	SF	22,0	15,0	-	G3/8	-	12,0	58,7	-	30	19	80 g

Example for ordering:	Type	+	Material no.	+	Code	=	Ordering no.
	092. 020	+	16	+	SD	=	092. 020. 16. SD

Flexible pneumatic tube

Material:
Rubber tube, covered by metal braid; steel core
Connections:
Air supply: 3/8 BSPP
Nozzle side: 1/4 BSPP
T_{max} = 100°C · p_{max} = 15 bar

Ordering no.	Length [mm]	Suitable for nozzle series
Z. SPZ. 150. 02. AE. AD. 0	150	600. 130 600. 283 600. 326
Z. SPZ. 300. 02. AE. AD. 0	300	
Z. SPZ. 450. 02. AE. AD. 0	450	

www.spray-expert.com